



## GENERAL SPECIFICATIONS \*

• L.O.A	19m	62'4"
• Hull length	17,60m	57'9"
• L.W.L.	17,00m	55'9"
• Beam	5,30m	17'5"
• Standard draft (L-keel)	2,55m	8'4"
• Standard ballast weight (Cast iron)	5 000kg	11,020 lbs
• Very deep draught keel (T-keel)	2,88m	9'5"
• Ballast weight (Cast iron)	5 000kg	11,020 lbs
• Air draft (excluding antennae)	27,31m	89'7"
• Performance air draught (excluding antennae)	28,41m	93'2"
• Light displacement	22 280kg	49,105 lbs
• Fuel capacity (standard)	500L	132 US Gal
• Fresh water capacity (standard)	860L	227 US Gal
• Engine power (Propeller shaft)	150 HP	150 HP

## ARCHITECTS / DESIGNERS

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

## EC CERTIFICATION \*

- Category A - 12 people
- Category B - 14 people
- Category C - 14 people

## STANDARD SAILS DIMENSIONS \*

### ALUMINUM CLASSIC MAST

• Mainsail	105,00m <sup>2</sup>	1,130 sq/ft
• Self-tacking jib	67,00m <sup>2</sup>	721 sq/ft
• Furling genoa (111 %)	84,00m <sup>2</sup>	904 sq/ft
• Code 0	155,00m <sup>2</sup>	1,668 sq/ft
• Asymmetric spinnaker	300,00m <sup>2</sup>	3,229 sq/ft
• Staysail	36m <sup>2</sup>	387 sq/ft
• I	23,60m	77'5"
• J	6,64m	21'9"
• P	23,00m	75'6"
• E	8,00m	26'3"

### CARBON CLASSICAL MAST (+ 1,10m / 3'7")

• Performance version mainsail	112,00m <sup>2</sup>	1,205 sq/ft
• Self-tacking jib	67,00m <sup>2</sup>	721 sq/ft
• Furling genoa (111 %)	84,00m <sup>2</sup>	904 sq/ft
• Code 0	165,00m <sup>2</sup>	1,776 sq/ft
• Asymmetric spinnaker	315,00m <sup>2</sup>	3,390 sq/ft
• Staysail	36m <sup>2</sup>	387 sq/ft
• I	23,60m	77'5"
• J	6,64m	21'9"
• P	24,00m	78'9"
• E	8,00m	26'3"



CONNECT YOUR BOAT FREE YOUR MIND

\* Provisional specifications, boat in process of certification.



## STANDARD EQUIPMENT

### CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Monolithic infusion hull
- Vacuum infused structural inner liner (Fabrics - resin) bonded to the hull
- Fibreglass, balsa wood, PET foam sandwich infusion deck with non-slip coating
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Twin rudders hung with stainless steel stock
- White coloured hull - Aluminum grey hull decoration
- 6 Hull portholes

### DECK EQUIPMENT

#### RIGGING

Depending on version:

- **Black lacquered aluminum classical mast** tapered, deck stepped,  
3 Aft swept spreaders, Sparcraft  
- C-strand Rigging
- **Axon Performance carbon classical mast** tapered, deck stepped (+ 1m / 3'3"), Weight saving: 100kg / 220 lbs)  
3 Aft swept spreaders  
- ROD Rigging
- Harken fixed blocks at foot of mast
- Harken Switch mainsail rail
- Black lacquered aluminium Canoë boom with LED lighting (warm white)
- Manual hydraulic unit: Double hydraulic textile backstay on 2 pistons + Hydraulic kicker tackle and foot tuning line on unit (4 Functions)
- Genoa tracks on the roof with traveller and hauling line controlled from the cockpit
- Electric genoa furler under deck
- 1 Mainsail attachment point at bottom of cockpit with Harken Flip-Flop block
- All lines brought back to the helm stations (except mainsail sheet and boom topping lift)
- Dyneema Complete running rigging:  
- Mainsheet halyard sheave block,  
- Genoa halyard,  
- Boom uphaul (polyester) with cleat on mast,  
- Mainsail sheet,  
- 2 Genoa sheets,  
- 2 Automatic reefing system, 1 manual reef
- Clutches: 6 to starboard, 4 to port
- Harken Black Magic blocks
- 2 Spinnaker sheet chain plates/code 0
- Running rigging hidden
- Lazy-jacks

#### HARKEN PERFORMA WINCHES

- 1 Mainsail sheet captive winch under cockpit floor
- 2 Electric Performa rigging winches (H50.2 STPE)
- 2 Performa electric genoa winches (H70.2 STPE)
- 2 Aluminum Speed Grip winch handles
- Stowage of which handles in dedicated space in rope bags

### SAILS

- Boast supplied without sail

### MOORING LINES - MOORING

- Polyester bowsprit (deco carbon) with integrated anchoring and bobstay with spinnaker chin plate (for Code 0 and asymmetric spinnaker)
- Self-draining chain locker, Clench bolt, Piston-driven cover
- Single roller stainless steel bow fitting
- 24 V - 2 000 W vertical electrical windlass - Remote control in mooring locker
- Deck wash electric pump in the chain locker (uses sea water or fresh water from tanks)
- 8 Black anodised aluminum mooring cleats (Length: 40 cm / 1'4")
- Stainless steel chafing plate

### SAIL LOCKER

Access through T70 deck hatch, Passage width: 0,65 x 0,65m / 2'2" x 2'2"

- Stainless steel ladder
- Shelving and stowage trays
- LED lighting
- 1 230 V socket

### SAFETY ON DECK

- 1 Black lacquered stainless steel open pulpit
- 2 Black lacquered stainless steel aft pulpits with integrated fairlead
- 1 Black lacquered stainless steel central aft pulpit (Height: 960mm / 3'2")
- 2 Black lacquered stainless steel handrails on the roof
- 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on deck
- Dual textile lifelines and black lacquered stainless steel stanchions (Height: 620mm / 2') - Side boarding gate on either side
- 1 Accommodation ladder
- Emergency ladder on pushpit

**BENETEAU****First 60**

Provisional Specifications - Europe

**COCKPIT**

- Self-draining cockpit
- Iro-Deck slatted
- 2 Sail lockers below cockpit seating
- 2 Service compartment accesses to aft
- 1 Access hatch to tender garage
- 2 Cockpit tables on black lacquered stainless steel fixed leg, solid natural wood top with 2 extensions, stainless steel cup holders on the ends with handrail function and 1 long full-length handrail (electric legs as an option)
- Charcoal Grey covers for cockpit tables
- Iro-Deck slatted cockpit benches
- Iro-Deck slatted side helmsman's seats, tilting according to the vessel's list
- Foldaway helmsman foot chock
- 2 Steering wheel consoles:
  - Black composite helm (diameter 1 100 mm/3'7") fixed on white lacquered aluminum pedestal
  - Steering gear at the helm station
  - Stainless steel steering chain transmission system
  - Black lacquered stainless steel hand rail
- 1 Emergency tiller
- 1 Steering compass on port console
- Engine throttle and control panel on starboard
- 1 PPMA folding companionway door in the bottom of the cockpit - Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Space for 12 place liferaft: 0,96 x 0,59 x 0,40m / 3'2" x 1'11" x 1'4")
- Courtesy lighting (7 LED lighting points, warm white lighting)
- 2 Waterproof exterior speakers (Fusion)

**Standard Offshore Garmin pack:**

- Port and starboard helm stations:
  - 1 12" multi-function touchscreen Map 1223 GPS (GPS, Chart plotter, Card reader - Bluechart G3 cartography included) on console
  - 1 GNX120 display located in front of the helm stations (under the winches)
- Wind Sensor gWind Race - pole 1m / 3'3": Windvane, Anenometer
- Reactor 40 Pilot with GHC 50 control on port console
- Wireless autopilot remote control
- Garmin Quatix 7 connected watch
- Airmar DST810 Sensor (Log, Speedometer, Temperature)
- PC interface (GND10)
- Fixed 315i VHF at chart table, without AIS receiver function
- Windex Windvane
- Protective covers for helm & consoles (Charcoal Grey)

**SWIM PLATFORM / AFT TRANSOM**

- Fully opening transom, convertible to bathing platform (2,73m x 1,00m / 8'11" x 3'3")
- 3 Folding access steps to the cockpit to starboard
- Electrically controlled opening on console
- Remote control opening of the aft platform
- Iro-Deck slatted swim deck
- 1 Detachable stainless steel bathing ladder with dedicated stowage in the tender garage

**TENDER GARAGE**

Accessible from the platform and from the cockpit

For storing a partially deflated tender, type Williams Minijet 280 (2,48 x 1,69 x 0,80 m/8'2" x 5'7" x 2'7") or Highfield classic (2,90 x 1,70 m/9'6" x 5'7")

- 1 Touch-operated ceiling LEDs
- Tender launching system, available as an option
- 1 Cockpit shower with mixer tap in the tender garage
- Fresh water inlet fed by the tanks for rinsing the tender

**INTERIOR**

- Teak or white wood woodwork
- Alpialready teak flooring
- Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- Beige padded ceilings and white lacquered wood in the central part of the saloon

**COMPANIONWAY**

Headroom: 2,05m / 6'9"

- Saloon companionway with 5 suspended Alpialready teak non-slip steps, LED lighting below each step
- 2 Leather-covered stainless steel handrails (DK02 - chocolat color)

**SALOON**

Headroom: 2,02m / 6'8"

- DK02 chocolate leather covered stainless steel handrails on the ceiling
- 2 T60 flush-fit deck hatches with blind/mosquito nets
- 4 Coachroof windows including 2 opening portholes
- 2 Long portholes with built-in blind
- Indirect LED lighting on the upper part of the portholes

**Port saloon:**

- Long U-shaped bench seat:
  - seats made from HR40 foam
  - soft seating thanks to the memory material trim + padding
- Saloon table with Alpi teak tabletop (fixed aluminium legs with carbon covering)
- Storage under bench seats
- Port-side electrical panel incorporated into furniture giving access to the electrical connections
- Indirect LED lighting below the bench seat and the upper part of the portholes
- 2 Flexible reading lights
- 1 Dual USB port (A-C)
- 1 230 V socket

**Starboard saloon:**

- 1 Sofa facing the saloon:
  - seats with HR26 and HR30 foam
  - softness thanks to the finish with hollow fibres + padding
  - 1 movable foot stool
- Stowage under the seating
- 1 Central locker with 2 drawers, bottle stowage

**Starboard chart table:**

- Opening lid - Valet tray - Storage - Moulded wood fiddle
- DK02 Chocolate leather swivel navigator seat
- Audio:
  - Fusion RA670 entertainment system
  - 2 B&W interior speakers + bass box in the saloon
- 1 Adjustable reading light
- 1 Dual USB port (A-C)
- 1 230 V socket

**GALLEY- FORWARD**

Headroom: 2,04 - 2,16m / 6'8" - 7'1"

- 2 part forward galley
- Corian Glacier White work top with moulded Apli teak beading
- 2 Coaming glazing
- LED strip light under the lockers

**To starboard:**

- 1 1 rectangular stainless steel sink (550 x 362 x 204mm / 1'10" x 1'2" x 8")
- 1 Mixer tap with hot/cold water under pressure
- 1 Eno Bretagne 3-ring gas stove 19 L thermostatic oven with stainless steel grill mounted on gimbals - Protection bar - Stowage below the oven with drop-down door
- Miele 230 extractor hood
- 1 3 doors 1 shelf 3 drawers unit
- Large storage below the floor with space for 18 bottles
- 1 20 L bin + 2 x 16 L for recycling
- Pillar with beige cover

**to port:**

- 24V 157L / 41 US Gal stainless steel fridge with front-opening door + 1 stainless steel built-in 75L / 20 US Gal fridge drawer compartment
- 1 75L / 20 US Gal deep freeze drawer (24V)
- Fitted lockers and closed shelving
- 1 3 drawers cabinet

**OWNER'S CABIN**

Headroom: 2,08 - 1,91m / 6'10" - 6'3"

- Double bit (2,00 x 1,60 - 1,01 m/6'7" x 5'3" - 3'7") with Moby 21 fabric padded headboard, accessible from both sides
- Large stowage area under the bed + 1 drawer on port side
- Sprung mattress (thickness: 180 mm/7")
- 2 Hanger closets, with incorporated LED lighting
- 2 Low units along the port side of the hull with large drawers
- Flexible and adjustable LED reading lights on the headboard
- 2 230V Sockets
- 2 Double USB sockets on the headboard
- Indirect lighting below the bed and ceilings
- 4 Overhead lights
- 2 T70 flush-fit deck hatches with blind/mosquito nets
- 1 T10 deck hatch with blind/mosquito net
- 2 Portholes with rigid sliding blind

**PRIVATE HEAD - OWNER'S CABIN**

To starboard

Headroom: 2,08 - 1,94m / 6'10" - 6'4"

- Separate shower with plexiglass door - Wooden seat - Wood shower tray
- Work top in Corian Glacier White
- 1 Integrated polyester basin - Mixer tap
- 1 Storage cabinet under washbasin
- 1 Full length mirror
- 1 Tecma fresh water/seawater electric WC
- 1 64 L / 17 US Gal rigid holding tank
- Toilet accessories
- 1 T10 deck hatch with blind/mosquito net
- LED indirect lighting + 2 Overhead lights
- 1 230 V socket

**PORT AFT CABIN - VIP**

Headroom: 1,96m / 6'6"

- 1 Double bed (2,00m x 1,55m / 6'7" x 5'1")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- 1 Opened compartment along the side of the hull
- 2 flexible and multi-directional reading lights at bedhead
- 1 dual USB port
- 1 230 V socket
- 1 Overhead light
- 1 Porthole with rigid sliding blind and indirect LED lighting
- 1 Opening coachroof window
- 1 Opening porthole beneath cockpit bench seat

**AFT PORT HEAD COMPARTMENT - VIP**

Headroom: 2,05m / 6'9"

Accessed via port side aft cabin

- Separate shower - 1 mixer tap - White polyester shower tray
- Glacier White corian work top with sink and mixer tap
- 1 Bathroom cabinet - 2 doors with mirror
- 1 Tecma fresh water/seawater electric WC
- 1 64 L / 17 US Gal rigid holding tank
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- LED indirect lighting + 2 Overhead lights
- 1 230 V socket

**STARBOARD AFT CABIN**

Headroom: 1,96m / 6'6"

- 1 Double bed (2,00m x 1,55m / 6'7" x 5'1")
- 1 Hanging locker (houses washer-dryer option), built-in LED lighting
- 1 Opened compartment along the side of the hull
- 1 Drawer under the bed
- 2 flexible and multi-directional reading lights at bedhead
- 1 dual USB port
- 1 230 V socket
- 1 Overhead light
- 1 Porthole with rigid sliding blind and indirect LED lighting
- 1 Opening coachroof window
- 1 Opening porthole beneath cockpit bench seat

**AFT STARBOARD HEAD COMPARTMENT**

Headroom: 2,05m / 6'9"

Access through saloon

- Separate shower - 1 Mixer tap - White polyester shower base
- Glacier White corian work top with sink and mixer tap
- 1 Tecma fresh water/seawater electric WC
- 1 64 L / 17 US Gal rigid holding tank
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- LED indirect lighting + 2 Overhead lights
- 1 230 V socket

**ENGINE**

- Engine Yanmar Diesel:
  - 150 HP, Propeller shaft, Common Rail
- Engine control at the starboard helm station - Control panel
- 24 V retractable bow thruster - Side Power - 8,7 CV - Thrust 160 kg
  - Diameter 250 mm + 4 Dedicated batteries (50Ah - 12V)
- Engine compartment:
  - Ventilation: 2 Air intakes and 1 powered air expulsion
  - Soundproofing foam: 40mm /  $1\frac{9}{16}$ "
  - LED lighting
- Engine data available on Yanmar screens at steering station and on Garmin screen
- 1 Alternator (12V / 130Ah)
- 2 2 x 250 L/2 x 66 US Gal aluminium diesel tanks (under saloon flooring) - Electronic gauge - Low level alarm - 1 Deck filler for each tank (to port)
- Filters: Seawater - Diesel - Water separator
- 4 folding blades propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Engine access through passageway and aft cabins, 1 Accessed via port side aft cabin

**PLUMBING**

- 4 Rotomoulded freshwater tanks 4 x 200L / 4 x 53 US Gal, under saloon floor, port and starboard - 2 Deck fillers to starboard (1 filler fills 2 tanks) - Crossover valves for the tanks below the floor in front of the companionway
- Pressurised electric water pump - Expansion tank - Inline filter
- 60 L / 16 US Gal Electric water heater (powered by the engine or shore power socket)
- 1 64 L/17 US Gal black water holding tank for each WC with electrical gauge
- Automatic shower draining pumps
- Deck wash electric pump in the chain locker (uses sea water or fresh water from tanks)
- 2 Electric bilge pumps
- 1 Manual bilge pump
- 1 Shore fresh water supply

**GAS**

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,28m / 11" x Height: 0,45m / 1'6")
- Regulator and safety tap
- Gas leak detector

**SMART BOARD**

"SEANAPPS" smart technology:

- For monitoring the boat's status and receiving alerts as well as maintenance advice via the associated mobile application.
- The type of information collected (GPS position, batteries, engine info, navigation data, etc.) varies according to the boat's configuration.

**seanapps**

CONNECT YOUR BOAT FREE YOUR MIND

**ELECTRICITY**

- 24 V electrical panel at chart table + Navicolor 3.5" screen (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + Single USB socket
- Wireless radio controlled switches (no battery) for the lighting
- 10" touchscreen on port bulkhead at bottom of companionway, dedicated to Ship Control, used to control all functions from the saloon
- **Ship Control technology** control numerous functions from the navigation screens (or from a tablet or smartphone using a dedicated app):
  - Anchoring and masthead navigation lights
  - Lighting of boom, spreaders (optional), underwater spotlights (optional)
  - Courtesy light in cockpit
  - Direct lighting
  - Deck searchlight
  - Inverter
  - Fridge
  - Water unit
  - Bilge pumps
  - Air conditioning (Option)
  - Generator (Option)
  - Audio
  - Control of levels (diesel, fresh water, black water)
  - Battery monitoring
- 24V circuit
- 2 000 W inverter
- 2 Lithium batteries (200Ah)

*The lithium batteries can be used in exactly the same way as the greater number of AGM batteries that they replace. Weight saving: Approximately 170 kg / 350 lbs. This technology allows 100% of the battery capacity to be used compared with 75% for the AGM batteries. The engine battery is still AGM.*

- 1 AGM engine battery (50Ah)
- 1 Alternator 24 V (85Ah)
- Battery cut-off switch easily accessible under the port aft cabin access step
- 1 Battery charger (24V - 100Ah)
- 1 Power distributor
- 12 230V Sockets:
  - 2 in the forward cabin
  - 1 in the heads
  - 1 in the aft cabins
  - 1 in the saloon (Port)
  - 1 at chart table
  - 4 in galley
  - 1 in the engine compartment
  - 1 in the sail locker
- 6 Dual USB socket - Dual USB port (A-C):
  - 2 in the forward cabin
  - 1 in the aft cabins
  - 1 at chart table
  - 1 on the electrical panel
- 1 Shore power socket 230 V, next to the port side helm station
- LED lighting:
  - Overhead lights, with dimmer
  - Reading lights
  - Indirect lighting, with dimmer
  - Side decks courtesy lighting
- LED navigation lights:
  - 1 Masthead light
  - 1 Steaming light
  - 1 Anchor light on masthead
- Deck searchlight (LED)
- Wire runs for option cables

**MISCELLANEOUS ITEMS**

- Smoke detector
- Cleaning kit: eco-friendly cleaning products kit

## PACKS

### FASTNET ELECTRONIC PACK (GARMIN)

---

- 3 GNX120 7" mast screens + mast bracket + cover
- 800 AIS
- GHS11 VHF Wired handset at port helm station

### RIGGING PACKS (Compatible with the 2 masts)

---

#### DOWNWIND PACK

- 2 Additional halyard clutches to starboard
- 2 HARKEN Black Magic blocks for spinnaker/code 0 sheet
- 1 HARKEN Black Magic block for spinnaker tack led back to the dedicated cleat in the cockpit
- 1 Dyneema halyard sheave with block for spinnaker or code 0
- 1 Dyneema halyard for asymmetric spinnaker
- 1 Spinnaker tackline with return on dedicated cleat in cockpit
- 2 Barber hauler (chain plate on bulwark) with jammer

#### STAYSAIL RIGGING PACK AND SELF-TACKING JIB

- 1 Wichard double chainplate on forward deck for removable forestay
- 1 Dyneema halyard sheave with block for staysail
- 1 Clutch, to starboard
- Self-tacking jib hardware: 1 Self-tacking jib track with traveller
- Staysail/self-tacking jib sheet with jammer to starboard

### NORTH SAILS SAIL PACK (NPL Tour, laminated, dark grey colour)

#### Aluminum sails mast pack

- Full-batten mainsail (105 m<sup>2</sup>/1 130 sq/ft) and Genoa on furler (84 m<sup>2</sup>/904 sq/ft)
- Charcoal Grey lazy bag

#### Carbon mast sails pack

- Full-batten mainsail (112 m<sup>2</sup>/1 205 sq/ft) and Genoa on furler (84 m<sup>2</sup>/904 sq/ft)
- Charcoal Grey lazy bag

#### MOORING PACK

- Delta 40 kg/88 lbs anchor (galvanized steel) (stainless steel anchor upgrade as an option)
- Chain (Diameter: 12mm /  $\frac{1}{2}$ " - Length: 70m / 230')
- Ropes (Diameter: 22mm /  $\frac{7}{8}$ " - Length: 50m / 164')
- 10 Fenders:
  - 4 XL (Diameter: 300mm / 12" - Length: 1 130mm / 3'8")
  - 6 L (Diameter: 300mm / 12" - Length: 880mm / 2'11")
- 4 Moorings lines (Diameter: 18mm /  $\frac{11}{16}$ " - Length: 15m / 49'3")
- Anchor positioner

#### MOORING PACK (inflatable)

- Delta 40 kg/88 lbs anchor (galvanized steel)
- Chain (Diameter: 12mm /  $\frac{1}{2}$ " - Length: 70m / 230')
- Ropes (Diameter: 22mm /  $\frac{7}{8}$ " - Length: 50m / 164')
- 8 Inflatable fenders (Diameter: 360mm / 1'2" - Length: 1 200mm / 3'11")
- 4 Moorings lines (Diameter: 18mm /  $\frac{11}{16}$ " - Length: 15m / 49'3")
- Anchor positioner

## OPTIONS

### NAVIGATION ELECTRONICS: GARMIN

- Garmin Black radar

### RIGGING

- FurlerBoom V-shaped furler boom, black lacquered (remove the Harken Switch mast rail and the trim of the hydraulic unit) - Not compatible with the North Sails sails

### NORTH SAILS SAILS

- Self-tacking jib with electric furling (NPL Tour, laminated, dark grey colour) + Self-tacking jib track and traveller. Sail Pack (For aluminium or carbon mast) - Remove the genoa included in the pack
- Self-tacking staysail with manual furling (NPL Tour, laminated, dark grey colour). Requires staysail rigging Pack
- Code 0 on electric furler (Hélix Cruising NPL - Grey)

### OUTSIDE PROTECTIONS

- Coachroof sprayhood, Lexan rigid glazing, Charcoal Grey
- Fold-back cockpit bimini with LED battery-powered lighting, Charcoal Grey
- Fold-back bimini for steering station with battery-powered LED lighting, Charcoal Grey
- Sunshade for the cockpit, Charcoal Grey (compatible with all booms)
- Sunshade on foredeck, Charcoal Grey

### MOORING LINES - MOORING

- Stainless steel upgrade to replace the galvanized anchor in the mooring packs
- 8 Retractable Nomen black anodised cleats (in lieu of standard)
- Retractable capstan (Bow)

### HULL - DECK - COCKPIT

- Retractable stern thruster
- Iro-Deck slatted side decks
- Iro-Deck slatted roof
- Integrated hydraulic gangway, on port
- Polyester folding gangway (2,60m / 8'6")
- Tender launching system (folding ramp with roller for recovering the aft platform, 1 manual winch) + Fresh water inlet fed by the tanks for rinsing the tender
- Outboard engine bracket
- Caron Y-shaped steering wheel
- 1,20 m/3'11" carbon flagstaff
- Metallic hull paint (Hull - Aft transom - Bowsprit) - Requires the teak slatted catwalks option
- Williams 280 Minijet tender - 80 HP

### WATER SYSTEM

- Seawater electric pump, in galley
- Watermaker (100 l/h / 26 US Gal/h - 24/230V)
- Deck washing pump in the tender garage

### EXTERIOR LIGHTING

- 4 Underwater lights (2 forward, 2 aft)
- LED spreader bar lighting for black lacquered classical mast
- LED spreader bar lighting for carbon mast

### COCKPIT COMFORT

- Loop Sand exterior cockpit upholstery:
  - seats and backs on the cockpit benches: Filter foam 80 mm/3" thickness (Density: 60F+20S)
  - helm seats
- Electrical bases + mattress for the 2 cockpit tables (for the sun deck bed function)

### INTERIOR EQUIPMENT

#### LAYOUT VERSIONS

- Skipper cabin replacing the sail locker of the foredeck:
  - Headroom: 1,85m / 6'1"
  - Access through T70 deck hatch
    - Stainless steel ladder,
    - 1 Access through T70 deck hatch,
    - 1 Bed (1,92 x 0,65 - 0,58m / 6'4" x 2'2" - 1'11") Foam mattress - PVC cover, Marlin Weiss,
    - Storage,
    - 1 Dual USB port (A-C),
    - 1 230 V socket,
    - 1 Overhead light,
    - Head separate from cabin with WC, washbasin, shower

#### AMBIANCE

- Choice of internal upholstery: fabric, nubuck leather
- Saloon table, adjustable wooden top, electric stainless steel legs or low-table function or additional lounge space (mattress included)

#### DOMESTIC APPLIANCES

- Dishwasher for 9 sets (230V)
- Wine cellar 19 bottles (230V)
- Built-in 22 L grill and microwave combined oven (230V)
- Washer dryer: 8 kg for washing, 5 for drying (230V)
- 75 L deep freeze compartment with built-in 230 V ice maker + dedicated 500 W inverter (replacing standard 75L / 12-24 deep freeze drawer)
- All-electric galley (Ceramic hob + Electric oven)

#### MULTIMEDIA

- TV pre-assembly on lifting system, in the saloon (recommended TV size: 46")
- TV pre-assembly, in the forward cabin (on forward bulkhead)
- Hifi: FUSION Apollo RA670 amp with subwoofers + B&W speakers in the owner cabin

#### ON BOARD COMFORT EQUIPMENT

- Air conditioning 56 000 BTU + Shore socket extension cord (15m / 49'3" - 32A)
- Generator (11 KVA, 230V, 50Hz)
- Safe, in the forward cabin
- Spring mattress in the aft cabins (thickness: 160mm / 6")
- Charcoal Grey lee cloth, in the starboard aft cabin
- Electric battery switch (connected to the Ship Control, controls powering on or shut-off of batteries remotely)
- Tableware kit - 6 people

#### SERVICE

- Commissioning (Canet or Les Sables d'Olonne)
- Premium Handover